

# FLANGED FITTING SIZING CHART

FLG. SIZE	FLG. O.D.	RECOMMENDED FLG. PIPE INSUL	LOWER THAN 250 LB. PRESSURE RATED FLANGED FITTINGS					
			1/2" THK	1" THK	1 1/2" THK	2" THK	2 1/2" THK	3" THK
1"	4 1/4"	4 1/8"	#13S	#15S	#17S	#18S	#19S	#20S
1 1/4"	4 5/8"	4"	#13S	#15S	#17S	#18S	#19S	#20S
1 1/2"	5"	5 1/8"	#15S	#17S	#18S	#19S	#20S	#21S
2"	6"	6 1/8"	#17S	#18S	#19S	#20S	#21S	#22S
2 1/2"	7"	6"	#17S	#18S	#19S	#20S	#21S	#22S
3"	7 1/2"	7"	#18S	#19S	#20S	#21S	#22S	#23S
3 1/2"	8 1/2"	8"	#19S	#20S	#21S	#22S	#23S	#24S
4"	9"	8"	#19S	#20S	#21S	#22S	#23S	#24S
5"	10"	9"	#20S	#21S	#22S	#23S	#24S	#25S
6"	11"	10"	#21S	#22S	#23S	#24S	#25S	#26S
8"	13 1/2"	14"	#24S	#25S	#26S	#27S	#28S	#29S
10"	16"	16"	#26S	#27S	#28S	#29S	#30S	#31S
12"	19"	19"	#29S	#30S	#31S	#32S	#33S	#34S
14"	21"	21"	#31S	#32S	#33S	#34S	#35S	#36S
16"	23 1/2"	24"	#34S	#35S	#36S	#37S	#38S	#39S
18"	25"	25"	#35S	#36S	#37S	#38S	#39S	#40S
20"	27 1/2"	28"	#38S	#39S	#40S	#41S	#42S	#43S
24"	32"	32"	#42S	#43S	#44S	#45S	#46S	#47S